



SPECIFICATION SHEET

SEBCO 100-300^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1

1022-12 (100 Watt)
120VAC-1A MAX
12VAC-8.33A MAX
1x10A
60 Hz
6.75" x 5" x 4.5"
10 LBS.

CLASS 1

1023-12 (150 Watt)
120VAC-1.4A MAX
12VAC-12.5A
1x15A
60 Hz
6.75" x 5" x 4.5"
10 LBS.

CLASS 1

1024-12 (250 Watt)
120VAC-2.3A MAX
12VAC-21A MAX
1x25A
60 Hz
6.75" x 5" x 4.5"
13 LBS.

CLASS 1

1101-12 (300 Watt)
120VAC-2.75A MAX
12VAC-25A MAX
1x25A
60 Hz
6.75" x 5" x 4.5"
13 LBS.