

Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

APPLICATION — The DCS Small Die Cast Area Light is designed for general-purpose area lighting. It is the perfect choice for lighting large open areas for safety and security. Wide roadway applications, parking areas, or even wall mount applications for security lighting are all suitable applications for this fixture. The small size and multiple mounting options make this fixture economical and versatile.

CONSTRUCTION — The housing and door frame are constructed of die cast aluminum. The flat tempered glass lens is sealed in place and a door gasket is provided for weather tight protection. ETL listed for wet locations.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, US Green, White. Custom colors available upon request.

OPTICAL SYSTEM — Made with a state of the art high performance reflectors that use high gloss components to achieve precise photometric distributions. The fixture is a full cut-off light fixture and is Dark-Sky Friendly in the horizontal position only.

ELECTRICAL SYSTEM — Available in 50W thru 175W standard metal halide, pulse-start metal halide, and high pressure sodium. Comes standard with a 4KV pulse rated mogul base socket. Each 60HZ CWA Multi-Tap¹, 480V, or 120V NPF (HPS Only) ballast is pre-wired and installed for convenience.


MOUNTING — Standard mounting options include 2", 8" and 10.75" Straight Arms with internal bolt guides for square and round pole mounting on shoe-box models. 2" Adjustable Slip Fitter and Yoke Mount available for floodlight models. Additional mounting options are available.



Small Die Cast Area Light DCS SERIES



Fixture shown with SSA Straight Arm which is ordered separately.



Series	Housing Height	Length & Width
DCS	6.25"	12.00" x 12.00"

ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

Example: **DCSB1AL1-PS-BZ**

DCSB1		Wattage/Source		Voltage	Pulse-Start	Finish
Series	Reflector	X 42W Compact Fluorescent ²	K 100W PS Metal Halide	1 Multi-Tap ¹	PS Pulse-Start	BK Black
DCSB1	A Standard Flood	H 50W PS Metal Halide	C 100W High Pressure Sodium	2 480V		BZ Bronze
	B Type IV Forward Throw	A 50W High Pressure Sodium	V 150W PS Metal Halide	3 120V NPF ³		GR OD Green
	C Parking / Roadway	J 70W PS Metal Halide	D 150W High Pressure Sodium			USG US Green
		B 70W High Pressure Sodium	L 175W Metal Halide			WH White
						SP Special ⁴

Accessories (Order as separate line items)

2AF 2" Adjustable Slip Fitter	S113 Small Back Side Shield
B15 Adjustable Yoke Mount	S106 Small Three Sided Back Side Shield
SSA-S⁵ 2" Straight Arm	S100 Small Vandal Shield
SSA-M 8" Straight Arm	S103 Small Wire Guard
SSA 10.75" Straight Arm	
P12KNK 1/2" Adjustable Knuck Fitter	
S146 Small Visor Shield	

DCS Small Die Cast Area Light

MOUNTING ACCESSORIES

2AF
2" Adjustable Slip Fitter



P12KNK
1/2" Adjustable Knuck Fitter



B15
Adjustable Yoke Mount



SSA-S, SSA-M, SSA
2", 8" and 10.75" Straight Arms



ADDITIONAL FIXTURE ACCESSORIES

S146
Small Visor Shield



S100
Small Vandal Shield



S113
Small Back Side Shield



S79
Small Wire Guard



S106
Small Three Sided Back Side Shield

