


RSP ROUND STRAIGHT POLE



Pole

The pole shaft is fabricated from hot rolled carbon steel having a minimum yield of 55,000 PSI and conforms to ASTM A500 grade C requirements. The shaft construction is a single piece of formed steel welded longitudinally. The hand hole is located 1' 6" above the pole base. A ground lug is provided standard.

Anchor Base

The anchor base is fabricated from a structural quality hot rolled carbon steel plate that has a minimum yield strength of 36,000 PSI. The anchor base telescopes the pole shaft and has a circumferential weld on the top and bottom.

Base Cover

A full base cover is provided which encapsulates the base plate and anchor bolts to provide a clean transition from pier to pole.

Finish

The pole is finished with a Super Durable Powdercoat Paint. Multiple colors available. Galvanizing and T-Guard treatments available upon request. Additional warranty extensions available with these treatments.

Round Straight Pole	Pole Height	Shaft Size	Wall Gauge	Direct Burial	Finish	Mounting	Max EPA (1.3 MPH Gust)			Bolt Circle	Anchor Bolt Size	Shipping Weight
							90 MPH	100 MPH	110 MPH			
RSP	10	3	11		(A)	(B)	11.3	9.0	7.2	7.5"	.75"x18"x3"	50 lbs
RSP	10	4	11		(A)	(B)	21.4	17.0	13.8	8"	.75"x18"x3"	69 lbs
RSP	15	3	11		(A)	(B)	6.5	4.9	3.7	7.5"	.75"x18"x3"	55 lbs
RSP	15	4	11		(A)	(B)	12.9	10.0	7.8	8"	.75"x18"x3"	96 lbs
RSP	20	3	11		(A)	(B)	3.5	2.4	1.6	7.5"	.75"x18"x3"	73 lbs
RSP	20	4	11		(A)	(B)	7.7	5.6	4.1	8"	.75"x18"x3"	135 lbs
RSP	20	4	11	DB	(A)	(B)	7.7	5.6	4.1	NA	NA	176 lbs
RSP	20	4	7		(A)	(B)	12.4	9.4	7.2	8"	.75"x18"x3"	157 lbs
RSP	20	4	7	DB	(A)	(B)	12.4	9.4	7.2	NA	NA	184 lbs
RSP	20	5	11		(A)	(B)	13.3	10.0	7.6	11"	1"x36"x4"	207 lbs
RSP	20	5	11	DB	(A)	(B)	13.3	10.0	7.6	NA	NA	228 lbs
RSP	20	5	7		(A)	(B)	21.0	16.3	12.8	11"	1"x36"x4"	218 lbs
RSP	20	5	7	DB	(A)	(B)	21.0	16.3	12.8	NA	NA	239 lbs
RSP	24	4	11		(A)	(B)	4.4	2.8	1.6	8"	.75"x30"x3"	163 lbs
RSP	24	4	7		(A)	(B)	8.0	5.7	4.0	11"	1"x36"x4"	183 lbs
RSP	24	5	11		(A)	(B)	8.3	5.8	3.9	11"	1"x36"x4"	243 lbs
RSP	24	5	7		(A)	(B)	15.3	11.5	8.6	11"	1"x36"x4"	331 lbs
RSP	30	5	11		(A)	(B)	4.7	2.7	1.2	11"	1"x36"x4"	278 lbs
RSP	30	5	7		(A)	(B)	9.5	6.6	4.4	11"	1"x36"x4"	383 lbs
RSP	35	5	7		(A)	(B)	5.7	3.4	1.6	11"	1"x36"x4"	436 lbs


Option Codes

(A) Finish

BK - Black
BZ - Bronze
GR - OD Green
WH - White
USG - US Green
GLV - Galvanized
GLVP - Galvanized & Painted
(must specify paint color - example: GLVP-BRZ)
TG - T-Guard Internal Coating
(must specify paint color - example: TG-BRZ)
SP - Special

(A) Mounting

T238 - 2 3/8" OD tenon (standard)
T278 - 2 7/8" OD tenon
T312 - 3 1/2" OD tenon
PC - Pole Cap Only
DM1 - Drill One Side
DM290 - Drill 2 Sides at 90°
DM2180 - Drill 2 Sides at 180°
DM390 - Drill 3 Sides at 90°
DM3120 - Drill 3 Sides at 120°
DM490 - Drill 4 Sides at 90°



*Anchor Bolts and Template can be pre-shipped at the customers' expense upon request.