LED FLEXBRITE KITS/CUSTOM CUT

Easy to use, flexible, dimmable LED rope light in Cool White, Warm White, and Ultra Warm White. Kits interconnect to build your own semi-custom CSA or UL Listed solution; or order UL2388 compliant sections custom cut to the nearest 36" increment.

Performance

- Line voltage kits are economical no drivers needed
- 3mm LEDs at 1" spacing emit up to 34 lumens per foot
- Dimmable with most electronic low voltage and LED/CFL dimmers* (minimum loads may apply)
- Suitable for indoor and outdoor use

Construction

- Each kit includes removable five foot power cord with 1.6A inverter and fused 120V AC 2-prong plug, removable cap on opposite end and 1 clip per foot of light
- 1" LED spacing in clear UV inhibited PVC housing with 3mm LEDs wired in series parallel (36 LEDs per series)

Installation

- Use clips to hold in place for most indirect view installations
- Clear plastic track should be used for direct view installations and when mounting to the underside of a shelf or ledge to prevent sagging
- Easy to install kits interconnect and plug into standard 120V AC receptacles

Custom Cut Program

- UL Listed for indoor and outdoor use
- Same specifications as ULRL-LED reels
- Custom cut to the nearest 36" increment
- Order track or clips separately as needed





Specifications

LR-LED (kits); ULRL-LED custom cuts
120V, 60Hz AC
CW, WW, and UWW
67+(UWW)/72+(WW)/75+(WH)
1W/ft
See individual product
See individual product
192 feet(kits); 150 feet(custom cut)
N/A
120°
5-100% with ELV/LED dimmers*
Clear PVC with UV inhibitor
UL or CSA Listed for wet locations**
1/2"Dia. x 1" LED spacing
Wall control
Clips or mounting track
Via LR-LED-EXT3 (kits only)
3mm LEDs, vertical mount
60,000 hrs

^{*}Per the NEC, switched wall outlets cannot be used with wall dimmers

^{**}CSA/UL Listing is void if product is cut









WARM WHITE KITS 3000K • 67CRI • 32Lm/ft UL Listed

UL Listed

LR-LED-WW-3 3ft

LR-LED-WW-9 9ft

LR-LED-WW-15 15ft

LR-LED-WW-30 30ft

LR-LED-WW-75 75ft

COOL WHITE KITS 6400K • 75CRI • 34Lm/ft UL Listed

LR-LED-CW-3 3ft LR-LED-CW-9 9ft LR-LED-CW-15 15ft LR-LED-CW-30 30ft LR-LED-CW-75 75ft ULTRA WARM WHITE KITS 2100K • 67CRI • 30Lm/ft CSA rated for Canada

LR-LED-UWW-CSA-3 3ft LR-LED-UWW-CSA-9 9ft LR-LED-UWW-CSA-15 15ft LR-LED-UWW-CSA-30 30ft COOL WHITE KITS 6400K • 75CRI • 34Lm/ft CSA rated for Canada

LR-LED-CW-CSA-3 3ft LR-LED-CW-CSA-9 9ft LR-LED-CW-CSA-30 30ft

Each kit includes LED Flexbrite, removable 5ft power cord with 1.6A inverter, removable end cap and one mounting clip per foot of light. Use kits in like sizes, kelvin temperatures may not match across different length kits.

LED FlexBrite Custom Cut -

ULRL-LED-UWW

Ultra Warm White, 2100K, 1W/ft, 30Lm/ft, 150ft max run

ULRL-CONKIT-LEDSHELL

(Required)
120V UL2388 compliant power
connection of 5ft cord with 1.6A
inverter and fused plug, and end cap

ULRL-LED-WW

Ultra Warm White, 3000K, 1W/ft, 30Lm/ft, 150ft max run

ULRL-CONKIT-LEDSHELL

(Required)

120V UL2388 compliant power connection of 5ft cord with 1.6A inverter and fused plug, and end cap

ULRL-LED-CW

Cool White, 6400K, 1W/ft, 34Lm/ft, 150ft max run

ULRL-CONKIT-LEDSHELL

(Required)

120V UL2388 compliant power connection of 5ft cord with 1.6A inverter and fused plug, and end cap

LED FlexBrite Accessories



LR-LED-EXT3

3ft jumper (linking) cable for LED rope light



RL-TRK-3

3ft clear plastic mounting track for LED or incandescent rope light (sold in cases of 40 only)

RL-TRACK-4

4ft clear plastic mounting track for LED or incandescent rope light



RL-CLIP/SCREW

Clear plastic "U" shaped mounting clip with (2) mounting screws for LED or incandescent rope light

LR-CLIP-20

(20) clear plastic "U" shaped mounting clips with (40) mounting screws for LED or incandescent rope light; blister pack