

HYBRID 2 KITS



ACCENT

HYBRID 2 KITS

Line voltage Hybrid 2 Kits are economical - no drivers needed - and link up to 150 feet. Interconnect multiple cETLus rated kits for high output applications, indoors and out.

Performance

- 120° beam angle provides even light distribution - perfect for coves and numerous accent lighting applications
- 5050 SMD LEDs emit up to 180 lumens per foot
- Dimmable with most incandescent, low voltage magnetic and low voltage electronic dimmers* (minimum loads may apply)
- Available in Bright White (5000K) and Warm White (2700K), in six interconnectable lengths that quickly twist and connect together, up to 150 feet

Construction

- Kits include a 5ft removable power cord, one removable end cap and one mounting clip per foot of length
- Flexible housing with clear PVC lens is protected with UV inhibitor
- Parallel wiring to each LED improves longevity

Installation

- Use clips to hold in place for most cove applications
- Clear plastic track or aluminum channel should be used when straight lines of light are needed or when mounting to the underside of a shelf or ledge to prevent sagging



Specifications

Series	H2-KIT
Input voltage	120V AC, 60Hz
Colors	2700K (WW) / 5000K (WH)
CRI	82
Wattage	3W/ft
Lumens	145Lm/ft (WW) / 180Lm/ft (WH)
Kit lengths	3ft, 6ft, 12ft, 18ft, 30ft, & 45ft
Maximum run	150 feet
Cuttability	N/A
Beam angle	120°
Dimming	10-100% with most dimmers*
Material	Clear PVC face, white back
Rating	cETLus Listed for wet locations**
Dimensions	9/16"W x 1/4"H
Switching	Wall control
Mounting	Clips, track, or channel
Linking	See jumpers on facing page
LED type	5050 SMD LEDs (20 per foot)
Rated life	30,000 hrs

*Per the NEC, switched wall outlets cannot be used with wall dimmers

**c/ETL/us Listing is void if product or its power cord is cut or altered

Hybrid 2 Kits



H2-KIT-3-WW (3ft length, 9W)
H2-KIT-6-WW (6ft length, 18W)
H2-KIT-12-WW (12ft length, 36W)
H2-KIT-18-WW (18ft length, 54W)
H2-KIT-30-WW (30ft length, 90W)
H2-KIT-45-WW (45ft length, 135W)
 2700K Warm White LEDs
 120V, 82 CRI, 145Lm/ft



H2-KIT-3-WH (3ft length, 9W)
H2-KIT-6-WH (6ft length, 18W)
H2-KIT-12-WH (12ft length, 36W)
H2-KIT-18-WH (18ft length, 54W)
H2-KIT-30-WH (30ft length, 90W)
H2-KIT-45-WH (45ft length, 135W)
 5000K Bright White LEDs
 120V, 82 CRI, 180Lm/ft

Hybrid 2 Kit Accessories



H2-KIT-JUMP.5 6in jumper cable
H2-KIT-JUMP3 3ft jumper cable
H2-KIT-JUMP6 6ft jumper cable
 Jumper (linking) cable
 with twist-and-tighten connectors;
 jumpers are inter-connectable



H2-TRACK-3
 3ft clear plastic mounting track
 5/8W x 5/16"H
 Sold in packs of 10 only



H2-CHAN-3
 3ft aluminum mounting track
 5/8W x 5/16"H
 Sold in packs of 10 only