# ETL COMMERCIAL GRADE LIGHT STRING

Popular decorative light strings that can interconnect via grounded plugs and sockets, while maintaining the cETLus safety rating for year-round use.

#### Performance

- Medium base sockets are spaced every 24" on center
- Suspended light string has a 2-3/4" lead from the top of the suspended socket to the center of the cable, available in White or Black
- Non-suspended light string is available in Black only
- 48ft light strings can support up to 1440 watts total (see Professional Decorative lamps and/or incandescent S14 lamps (no lamps are included with light string)

### Construction

- 14AWG SJTW 3-wire cable with grounded plug and socket allow multiple light strings to be interconnected
- Formulated PVC sockets form a tight seal around the bulb to preclude the entrance of water and moisture
- Suspended socket has T-mold with mounting hole and non-suspended has two mounting ears built into the base

#### Installation

- For spans up to 20 feet, use eyebolts and plastic ties to anchor ends
- For longer spans, use catenary cable (guy wire) with plastic ties at each socket
- Do not exceed 1440 watts in any single run
- Cutting the cable will void the c/ETL/us listing
- Be sure to fill every socket with a lamp
- Use end cover at the end of the last light string to keep out water

## Specifications

Series	ETLS
Input voltage	120V AC, 60Hz
Color temperature	N/A
CRI	N/A
Maximum run	1440W; 10 light strings max when
	using LED lamps
Beam angle	N/A
Dimming	Depends on lamps used
Material	PVC sockets, 3-C SJTW 14AWG cable
Cuttability	Non-rated if cut
Rating	c/ETL/us for wet locations
Dimensions	As noted
Switching	Wall control or branch circuit
Mounting	Catenary wire (optional)
Linking	Directly end-to-end or with
	outdoor rated extension cables
Rated life	Depends on lamps used

# ETL Commercial Grade Light String



ETL Listed Commercial Grade Light String, 24" spacing (40W max/socket), 14AWG SJTW 3-wire cable, male/female ends. \*Photos are for representational purposes and do not display actual socket spacing ETLS-MS-24-48-BK 48ft (24 sockets) ETL Suspended Medium Base Light String - Black Interconnectable up to 1440W

ETLS-MS-24-48-WH 48ft (24 sockets) ETL Suspended Medium Base Light String - White Interconnectable up to 1440W

