# **AREA LIGHTS** AL-10-LGP SERIES



#### **SPECIFICATIONS**

**CONSTRUCTION:** Formed solid brass pedestal mount lantern

LENS: Gold iridescent glass; optional plastic White Cracked Ice available (-ICE)

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (50w max.)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or

3w 50,000 hours average rating OMNI-3 LED (-LED3)

**SOCKET:** Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v, both with 200°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

MOUNTING: Hardware mounting kit supplied FINISH: Unfinished brass. Optional finishes available.



#### **Supplied Mounting Kit:**

1x- Mounting plate

3x- Blue 1/4" anchors

3x-#10 1" Steel sink phillips screws 2x-Washers

2x- Brass thumb screws

#### **ORDERING INFORMATION**

| CATALOG NO. DESCRIPTION |                              | LAMP         | SHIP WEIGHT |  |  |
|-------------------------|------------------------------|--------------|-------------|--|--|
| AL-10-LGP-BRS           | Brass Pedestal Mount Lantern | 18w S8 #1141 | 4.0 lbs     |  |  |

### 120v COMPACT FLUORESCENT PEDESTAL LANTERNS:

LAMP: 5w or 7w CFL T4 single tube, 4100K 10,000 hour (7w max.)


LAMP OPTIONS: 13w, 18w or 26w self ballasted CFL spiral GU24 2-Pin, 2700K (26w max.) BALLAST: For 5w and 7w models only - Internal Type 1 outdoor magnetic clamped core ballast. 120v primary amp draw of 0.165, not including lamp wattage. 5w and 7w CFL operate off same ballast and are interchangeable. 240v and 277v options available.

Consult factory for details.

SOCKET: G23 2-pin for 5w and 7w models; GU24 2-pin for Spiral GU24

| AL-10-LGPFL5-BRS   | Brass Pedestal Mount Lantern | 5w, 4100K CFL         | 4.0 lbs. |
|--------------------|------------------------------|-----------------------|----------|
| AL-10-LGPFL7-BRS   | Brass Pedestal Mount Lantern | 7w, 4100K CFL         | 4.0 lbs. |
| AL-10-LGPFL13S-BRS | Brass Pedestal Mount Lantern | 18w, 2700K CFL Spiral | 2.0 lbs. |
| AL-10-LGPFL18S-BRS | Brass Pedestal Mount Lantern |                       | 2.0 lbs. |
| AL-10-LGPFL26S-BRS | Brass Pedestal Mount Lantern |                       | 2.0 lbs. |


## LIGHT DISTRIBUTIONS AND PHOTOMETRICS




AL-10-LGP

Half Spread Photometrics 12 ft. (3.7m) diameter 36" above grade









|                 |       | LISTED |
|-----------------|-------|--------|
| JOB INFORMATION |       |        |
| Type:           | Date: |        |
| Job Name:       |       |        |
| Cat. No.:       |       |        |
| Lamp(s):        |       |        |
| Specifier:      |       |        |
| Contractor:     |       |        |
| Notes:          |       |        |
|                 |       |        |
|                 |       |        |

|                  |           | Texture |      | Iron | Brown | Stucco | Verde | Powder | Rust     | Verde    | Treatment |
|------------------|-----------|---------|------|------|-------|--------|-------|--------|----------|----------|-----------|
| -BLT -ATV -BRT - | -CAM -WTX | -нтх    | -RST | -WIR | -WBR  | -STU   | -RBV  | -CPR   | -BAR/CAR | -BAV/CAV | -BAT      |

AL-10-LGPCutSheet\* 060214

**BRASS & COPPER ONLY**