LED STEP LIGHTS SL-02-LEDP SERIES

GOGREEN

SPECIFICATIONS

CONSTRUCTION: Stamped aluminum, brass, copper or stainless steel (-SS available only on SL-02 4 louver model) step/brick light with stamped stainless steel surface mounting bracket

3 LENS OPTIONS:

SL-02-LEDP: Standard white acrylic; creates warm 2700K incandescent like color SL-02-LEDP-SB: Sand Blast clear acrylic; creates soft 3000K halogen like color

SL-02-LEDP-CL: Clear acrylic; bright halogen 3000K color **GASKET:** Black neosponge closed cell; .190" thickness

LIGHT SOURCE: 12v, 4w integrated LED flat panel with external driver, warm white 3000K

350 lumens (3000K) / 380 lumens (5200K)

LIFETIME RATING: 50,000 hours

SOCKET: None

DRIVER: 4w output, 12v AC input. Maximum distance from fixture is 18 feet.

For use with magnetic transformers only

VOLTAGE RANGE: 9 to 18 volts. Optimum operating range of 10 to 15 volts for consistent

performance and brightness.

WIRING: Red(+) and Black(-) 18 gauge zip cord from LED panel. Connects to external driver

Red(+) and Black(-) 18 gauge zip cord.

Additional 6' 18/2 zip cord supplied for wiring external driver to main cable.

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from LED driver to main cable

(12/2, 10/2 or 8/2 only)

MOUNTING: Stainless Steel surface mount bracket; four screws and wall anchors provided; Face plate attaches to bracket with two provided screws

FINISH: Aluminum - Black texture polyester powder coat; optional finishes available

Brass - Unfinished; optional finishes available

Copper-Unfinished; optional finishes available

ORDERING INFORMATION

Stainless Steel-Brushed

CATALOG NO.

SL-02-LEDP-BLT

SL-02-LEDP-BRS

SL-02-LEDP-COP

SL-02-AL-LEDP-BLT

SL-02-AL-LEDP-BRS

SL-02-AL-LEDP-COP

SL-02-1L-LEDP-BLT

SL-02-1L-LEDP-BRS

SL-02-1L-LEDP-COP

4.75"

SL-02-LEDP-SS

CAUTION: MUST BE POWERED BY LOW VOLTAGE AC MAGNETIC TRANSFORMER ONLY

SL-02: Mounting Holes on all models 3-5/16" on center

DESCRIPTION

Aluminum 4 Louver Brick Light

Stainless Steel 4 Louver Brick Light

Brass 4 Louver Brick Light

Copper 4 Louver Brick Light

Aluminum Lensed Brick Light

Aluminum 1 Louver Brick Light

Lenses are all standard white acrylic; creates warm 2700K incandescent like color Add -SB To Part #: Sand Blast clear acrylic; creates soft 3000K halogen like color

> 4.75" 121mm

Brass Lensed Brick Light

Copper Lensed Brick Light

Brass 1 Louver Brick Light

Add -CL To Part #: Clear acrylic; bright halogen 3000K color Add -52 To Part #: 5200K Cool White Flat Panel LED

Copper 1 Louver Brick Light





SL-02-LEDPCAM






SL-02-LEDPBRS



SL-02-1LLEDPBAR



		Intertek
JOB INFORMATION		
Туре:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		

SL-02-LEDP	† SL-02-AL-LEDP	3" 4 16mm SL-02-1L-LEDP	Specifier: Contractor: Notes:

LAMP

4w Flat Panel LED

SHIP WEIGHT

2.0 lbs.

_1.75"

	(Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment
	-BLT	-ATV	-BRT	-САМ	-WTX	-нтх	-RST	-WIR	-WBR	-STU	-RBV	-CPR		-BAR/CAR	-BAV/CAV	-BAT
SL-02-LEDPCutSheet 121015										BRASS	S & COPPER ONI	Υ				