LED COMMERCIAL STEP LIGHT SL-30-LEDP

GOGREEN

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or brass 1 louver step light with integrated LED panel and heat sink - no back box or mounting brackets required.

SL-30-LEDP: Standard white acrylic; creates warm 2700K incandescent like color SL-30-LEDP-SB: Sand Blast clear acrylic; creates soft 3000K halogen like color SL-30-LEDP-CL: Clear acrylic; bright halogen 3000K color

GASKET: Black neosponge closed cell; .190" thickness

LIGHT SOURCE: 12v, 4w integrated LED flat panel with external driver, warm white 3000K

350 lumens (3000K) / 380 lumens (5200K)

LIFETIME RATING: 50,000 hours

SOCKET: None

DRIVER: 4w output, 12v AC input. Maximum distance from fixture is 18 feet.

For use with magnetic transformers only

VOLTAGE RANGE: 9 to 18 volts. Optimum operating range of 10 to 15 volts for consistent

performance and brightness.

WIRING: Red(+) and Black(-) 18 gauge zip cord from LED panel. Connects to external driver

Red(+) and Black(-) 18 gauge zip cord.

Additional 6' 18/2 zip cord supplied for wiring external driver to main cable.

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from LED driver to main cable

(12/2, 10/2 or 8/2 only)

MOUNTING: Two matching #8 screws and wall anchors provided

FINISH: Aluminum - Black texture polyester powder coat; optional finishes available


Brass - Unfinished; optional finishes available

CAUTION: MUST BE POWERED BY LOW VOLTAGE AC MAGNETIC TRANSFORMER ONLY

ORDERING INFORMATION									
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT						
SL-30-LEDP-BLT	Cast Aluminum 1 Louver Step Light	4w Flat Panel LED	2.0 lbs.						
SI -30-I FDP-RRS	Cast Brass 1 Louver Step Light	4w Flat Panel LFD	4 0 lbs						

Lenses are all standard white acrylic; creates warm 2700K incandescent like color Add -SB To Part #: Sand Blast clear acrylic; creates soft 3000K halogen like color Add -CL To Part #: Clear acrylic; bright halogen 3000K color

Add -52 To Part #: 5200K Cool White Flat Panel LED



Mounting Holes 3.5" on center





SL-30-LEDP

IP66	CE	c Us
	•	Intertek

Date:	
	Date:

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

TYPF

LED COMMERCIAL STEP LIGHT SL-30 -LEDP GOGREEN

LIGHTING DISTRIBUTIONS AND PHOTOMETRICS

