## LED COMMERCIAL BRICK LIGHT **SL-31-LEDP SERIES**

## GOGREEN

#### **SPECIFICATIONS**

CONSTRUCTION: Cast aluminum or brass1 louver brick light with stamped stainless steel surface mounting bracket - no back box required.

SL-31-LEDP: Standard white acrylic; creates warm 2700K incandescent like color SL-31-LEDP-SB: Sand Blast clear acrylic; creates soft 3000K halogen like color SL-31-LEDP-CL: Clear acrylic; bright halogen 3000K color

GASKET: Black neosponge closed cell; .190" thickness

LIGHT SOURCE: 12v, 8w integrated LED flat panel with external driver, warm white 3000K

630 lumens (3000K) / 680 lumens (5200K)

LIFETIME RATING: 50,000 hours

**SOCKET:** None

DRIVER: 8w output, 12v AC input. Maximum distance from fixture is 18 feet.

For use with magnetic transformers only

**VOLTAGE RANGE:** 9 to 18 volts. Optimum operating range of 10 to 15 volts for consistent performance and brightness.

WIRING: Red(+) and Black(-) 18 gauge zip cord from LED panel. Connects to external driver

Red(+) and Black(-) 18 gauge zip cord.

Additional 6' 18/2 zip cord supplied for wiring external driver to main cable.

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from LED driver to main cable (12/2, 10/2 or 8/2 only)

MOUNTING: Stainless Steel surface mount bracket; two screws and wall anchors provided;

Face plate attaches to bracket with two provided set screws FINISH: Aluminum - Black texture polyester powder coat; optional finishes available


Brass - Unfinished; optional finishes available

#### CAUTION: MUST BE POWERED BY LOW VOLTAGE AC MAGNETIC TRANSFORMER ONLY


ORDERING INFORMATION										
CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT							
SL-31-LEDPBLT	Cast Aluminum 1 Louver Brick Light	8w Flat Panel LED	3.0 lbs.							
SL-31-LEDPBRS	Cast Brass 1 Louver Brick Light	8w Flat Panel LED	7.0 lbs.							

Lenses are all standard white acrylic; creates warm 2700K incandescent like color Add -SB To Part #: Sand Blast clear acrylic; creates soft 3000K halogen like color

Add -CL To Part #: Clear acrylic; bright halogen 3000K color Add -52 To Part #: 5200K Cool White Flat Panel LED










JOB INFORMATION		
Туре:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		

Black Texture (Standard)		Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR		-BAR/CAR	-BAV/CAV	-BAT
SL-31-LEDP Cut Sheet 121015									BRAS	S & COPPER ONI	Υ				


#### TYPF

# LED COMMERCIAL BRICK LIGHT SL-31-LEDP SERIES GOGREEN

### LIGHTING DISTRIBUTIONS AND PHOTOMETRICS



**SL-31** Half Spread Photometrics



**SL-31** Half Spread Photometrics

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Terra Cotta	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-TRC	-BAR/CAR	-BAV/CAV	-BAT
SL-31-LEDP Cut Sheet 121015										Υ					