

# 12V AC/DC INPUT LED DRIVERS DIRECT BURIAL RATED

**TYPE**

## HW-12-535012LED (for 4w & 5w LED Panels)

Output Power:	5w
Input Voltage:	9v to 15v AC/DC
Output Voltage:	12v DC
Output current:	350mA
Dimmable:	Yes, Standard MLV TRIAC Dimmer
Potted:	Yes
Case:	Anodized Aluminum
Dimensions:	1" OD x .75"
Input wire size:	18 AWG, 6" length
Output wire size:	18 AWG, 6" length
Input wires color:	Blue (no polarity)
Output wires color:	Red ( + ) / Black ( - )
Installation:	Direct Burial Rated
Warranty:	5 years
Listings:	UL8750, FCC Compliant

## HW-12-1070012LED (for 8w LED Panels)

Output Power:	10w
Input Voltage:	9v to 15v AC/DC
Output Voltage:	12v DC
Output current:	700mA
Dimmable:	Yes, Standard MLV TRIAC Dimmer
Potted:	Yes
Case:	Anodized Aluminum
Dimensions:	1" OD x .75"
Input wire size:	18 AWG, 6" length
Output wire size:	18 AWG, 6" length
Input wires color:	Blue (no polarity)
Output wires color:	Red ( + ) / Black ( - )
Installation:	Direct Burial Rated
Warranty:	5 years
Listings:	UL8750, FCC Compliant

## ORDERING INFORMATION

CATALOG NO.	DESCRIPTION
HW-12-535012LED	5w 300mA, 12v AC/DC Input LED Driver
HW-12-1070012LED	7w 700mA, 12v AC/DC Input LED Driver



### JOB INFORMATION

Type:	Date:
Job Name:	
Cat. No.:	
Lamp(s):	
Specifier:	
Contractor:	
Notes:	