



## SPECIFICATION SHEET

# SEBCO 100-300<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
PRIMARY VOLTAGE  
OUTPUT VOLTAGE  
BREAKERS  
FREQUENCY  
DIMENSIONS  
WEIGHT

#### CLASS 1

1022-12 (100 Watt)  
120VAC-1A MAX  
12VAC-8.33A MAX  
1x10A  
60 Hz  
6.75" x 5" x 4.5"  
10 LBS.

#### CLASS 1

1023-12 (150 Watt)  
120VAC-1.4A MAX  
12VAC-12.5A  
1x15A  
60 Hz  
6.75" x 5" x 4.5"  
10 LBS.

#### CLASS 1

1024-12 (250 Watt)  
120VAC-2.3A MAX  
12VAC-21A MAX  
1x25A  
60 Hz  
6.75" x 5" x 4.5"  
13 LBS.

#### CLASS 1

1101-12 (300 Watt)  
120VAC-2.75A MAX  
12VAC-25A MAX  
1x25A  
60 Hz  
6.75" x 5" x 4.5"  
13 LBS.



## SPECIFICATION SHEET

# SEBCO 500-600<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
PRIMARY VOLTAGE  
OUTPUT VOLTAGE  
BREAKERS  
FREQUENCY  
DIMENSIONS  
WEIGHT

#### CLASS 1

1025-12 (500 Watt)  
120VAC-5A MAX  
12VAC-42A MAX  
2x25A  
60 Hz  
8.25" x 5.75" x 5"  
19 LBS.

#### CLASS 1

1102-12 (600 Watt)  
120VAC-5.5A MAX  
12VAC-50A MAX  
2x25A  
60 Hz  
8.25" x 5.75" x 5"  
22 LBS.



## SPECIFICATION SHEET

# SEBCO 750<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

### CLASS 1

PART NUMBER	1026-12 (750 Watt)
PRIMARY VOLTAGE	120VAC-7A MAX
OUTPUT VOLTAGE	12VAC-63A MAX
BREAKERS	3x25A
FREQUENCY	60 Hz
DIMENSIONS	8.625" x 4.875" x 4.25"
WEIGHT	20 LBS.



## SPECIFICATION SHEET

# SEBCO 900-1000<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
PRIMARY VOLTAGE  
OUTPUT VOLTAGE  
BREAKERS  
FREQUENCY  
DIMENSIONS  
WEIGHT

#### CLASS 1

1103-12 (900 Watt)  
120VAC-8.25A MAX  
12VAC-75A MAX  
3x25A  
60 Hz  
10.25" x 5.625" x 5.25"  
28 LBS.

#### CLASS 1

1027-12 (1000 Watt)  
120VAC-10A MAX  
12VAC-84A MAX  
4x25A  
60 Hz  
10.25" x 5.625" x 5.25"  
28 LBS.