



## SPECIFICATION SHEET

# SEBCO 250<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
PRIMARY VOLTAGE  
OUTPUT VOLTAGE  
BREAKERS  
FREQUENCY  
DIMENSIONS  
WEIGHT

**CLASS 1**  
1062-12 (250 Watt)  
230VAC-1.2A MAX  
12VAC-21A MAX  
1x25A  
50 Hz  
6.75" x 5" x 4.5"  
13 LBS.

**CLASS 1**  
1062-24 (250 Watt)  
230VAC-1.2A MAX  
24VAC-10.5A MAX  
1x12A  
50 Hz  
6.75" x 5" x 4.5"  
13 LBS.



## SPECIFICATION SHEET

# SEBCO 500<sup>WATT</sup>



### FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

### REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
PRIMARY VOLTAGE  
OUTPUT VOLTAGE  
BREAKERS  
FREQUENCY  
DIMENSIONS  
WEIGHT

**CLASS 1**  
1063-12 (500 Watt)  
230VAC-2.4A MAX  
12VAC-42A MAX  
2x25A  
50 Hz  
8.25" x 5.75" x 5"  
19 LBS.

**CLASS 1**  
1063-24 (500 Watt)  
230VAC-2.4A MAX  
24VAC-21A MAX  
1x25A  
50 Hz  
8.25" x 5.75" x 5"  
22 LBS.



SPECIFICATION SHEET



# SEBCO 1000<sup>WATT</sup>

## FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

## REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER  
 PRIMARY VOLTAGE  
 OUTPUT VOLTAGE  
 BREAKERS  
 FREQUENCY  
 DIMENSIONS  
 WEIGHT

**CLASS 1**  
 1065-12 (1000 Watt)  
 230VAC-5A MAX  
 12VAC-84A MAX  
 4x25A  
 50 Hz  
 10.25" x 5.625" x 5.25"  
 28 LBS.

**CLASS 1**  
 1065-24 (1000 Watt)  
 230VAC-5A MAX  
 24VAC-42A MAX  
 2x25A  
 50 Hz  
 10.25" x 5.625" x 5.25"  
 28 LBS.