



SPECIFICATION SHEET

SEBCO 100-300^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1

1104-12 (100 Watt)
277VAC-1A MAX
12VAC-8.33A MAX
1x10A
60 Hz
6.75" x 5" x 4.5"
10 LBS.

CLASS 1

1105-12 (300 Watt)
277VAC-2.75A MAX
12VAC-25A
1x25A
60 Hz
6.75" x 5" x 4.5"
12 LBS.



SPECIFICATION SHEET

SEBCO 100-300^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS.
230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1

1104-24 (100 Watt)
277VAC-1A MAX
24VAC-4.2A MAX
1x5A
60 Hz
6.75" x 5" x 4.5"
10 LBS.

CLASS 1

1105-24 (300 Watt)
277VAC-1.2A MAX
24VAC-12.5A
1x15A
60 Hz
6.75" x 5" x 4.5"
12 LBS.



SPECIFICATION SHEET

SEBCO 500-600^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1
1106-12 (500 Watt)
277VAC-2A MAX
12VAC-42A MAX
2x25A
60 Hz
8.25" x 5.75" x 5"
19 LBS.

CLASS 1
1130-12 (600 Watt)
277VAC-2.5A MAX
12VAC-50A MAX
2x25A
60 Hz
8.25" x 5.75" x 5"
22 LBS.



SPECIFICATION SHEET

SEBCO 500-600^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1
1106-24 (500 Watt)
277VAC-2A MAX
24VAC-21A MAX
1x25A
60 Hz
8.25" x 5.75" x 5"
19 LBS.

CLASS 1
1130-24 (600 Watt)
277VAC-2.5A MAX
24VAC-25A MAX
1x25A
60 Hz
8.25" x 5.75" x 5"
22 LBS.



SPECIFICATION SHEET

SEBCO 750^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

CLASS 1

PART NUMBER	1131-12 (750 Watt)
PRIMARY VOLTAGE	277VAC-3A MAX
OUTPUT VOLTAGE	12VAC-63A MAX
BREAKERS	3x25A
FREQUENCY	60 Hz
DIMENSIONS	8.625" x 4.875" x 4.25"
WEIGHT	20 LBS.



SPECIFICATION SHEET

SEBCO 750^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

CLASS 1

PART NUMBER	1131-24 (750 Watt)
PRIMARY VOLTAGE	277VAC-3A MAX
OUTPUT VOLTAGE	24VAC-32A MAX
BREAKERS	2x15A
FREQUENCY	60 Hz
DIMENSIONS	8.625" x 4.875" x 4.25"
WEIGHT	20 LBS.



SPECIFICATION SHEET

SEBCO 1000^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
PRIMARY VOLTAGE
OUTPUT VOLTAGE
BREAKERS
FREQUENCY
DIMENSIONS
WEIGHT

CLASS 1
1132-12 (1000 Watt)
277VAC-4A MAX
12VAC-84A MAX
4x25A
50 Hz
10.25" x 5.625" x 5.25"
28 LBS.

CLASS 1
1132-24 (1000 Watt)
230VAC-4A MAX
24VAC-42A MAX
2x25A
50 Hz
10.25" x 5.625" x 5.25"
28 LBS.