

#### SPECIFICATION SHEET

### SEBCO 100-300



#### **FEATURES**

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- 60 WATT MAX CLASS "2" LISTED OUTPUTS
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET *CE* REQUIREMENTS

#### REQUIREMENTS

• LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838



- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

## PART NUMBER PRIMARY VOLTAGE OUTPUT VOLTAGE BREAKERS FREQUENCY DIMENSIONS WEIGHT

CLASS 2 1107 (100 Watt) 120VAC-1A MAX 12VAC-8.33A MAX 2x5A 60 Hz 6.75" x 5" x 4.5" 10 LBS.

1108 (150 Watt) 120VAC-1.4A MAX 12VAC-12.5A 3x5A 60 Hz 6.75" x 5" x 4.5" 10 LBS.

CLASS 2

CLASS 2 1109 (250 Watt) 120VAC-2.3A MAX 12VAC-21A MAX 4x5A 60 Hz 6.75" x 5" x 4.5" 13 LBS. CLASS 2 1123 (300 Watt) 120VAC-2.75A MAX 12VAC-25A MAX 5x5A 60 Hz 6.75" x 5" x 4.5" 13 LBS.



#### SPECIFICATION SHEET

### SEBCO 500 WATT



#### **FEATURES**

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- 60 WATT MAX CLASS "2" LISTED OUTPUTS
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET *CE* REQUIREMENTS

#### REQUIREMENTS

• LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838



- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

# PART NUMBER PRIMARY VOLTAGE OUTPUT VOLTAGE BREAKERS FREQUENCY DIMENSIONS WEIGHT

CLASS 2 1110 (500 Watt) 120VAC-5A MAX 12VAC-42A MAX 8x5A (AUTO) 60 Hz 8.25" x 5.75" x 5" 19 LBS.