



SPECIFICATION SHEET



SEBCO 100-300 WATT

FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- 96 WATT MAX CLASS "2" LISTED OUTPUTS
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER
 PRIMARY VOLTAGE
 OUTPUT VOLTAGE
 BREAKERS
 FREQUENCY
 DIMENSIONS
 WEIGHT

CLASS 2	CLASS 2
1104-24-2 (100 Watt)	1105-24-2 (300 Watt)
277VAC-1A MAX	277VAC-1.2A MAX
24VAC-4.2A MAX	24VAC-12.5A
1x4A Auto	3x4A Auto
60 Hz	60 Hz
6.75" x 5" x 4.5"	6.75" x 5" x 4.5"
10 LBS.	13 LBS.



SPECIFICATION SHEET

SEBCO 500^{WATT}



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE, WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- 96 WATT MAX CLASS "2" LISTED OUTPUTS
- SOME 120 VOLT TRANSFORMERS AVAILABLE WITH PRIMARY LINE CORD.
- BUILT IN THE USA TO THE HIGHEST STANDARDS
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS. 230 VAC TRANSFORMERS MEET CE REQUIREMENTS

REQUIREMENTS



- LISTED TO THE NEWEST UL STANDARDS 2108 AND 1838
- MANDATORY SECONDARY PROTECTION, AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411, (1993, 1996, 1999, 2002, 2005 AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET "SYSTEM" REQUIREMENTS, AS LONG AS ALL PARTS LISTED TO SAME ANSI/UL STANDARD

PART NUMBER	1106-24-2 (500 Watt)
PRIMARY VOLTAGE	277VAC-2A MAX
OUTPUT VOLTAGE	24VAC-21A MAX
BREAKERS	5x4A (AUTO)
FREQUENCY	60 Hz
DIMENSIONS	8.25" x 5.75" x 5"
WEIGHT	19 LBS.