SURFACE STEP LIGHTS SL-07 SERIES



SPECIFICATIONS

CONSTRUCTION: Cast aluminum, cast brass or 316 Stainless Steel "Hockey Puck" style

LENS: Sand blasted tempered flat glass

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (25w max)

LAMP SUPPLIED -MR8 MODELS: 20w MR8 FL; 2000 hours average rating (20w max)

LAMP OPTIONS: We recommend 10,000 hours average rating Xenon (-X) or Halogen (-H) or

3w 50,000 hours average rating OMNI-3 LED (-LED3)

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v; both with 200°C silicone lead wires

SOCKET -MR8 MODELS: High temp ceramic GU5.3 bi-pin with 250°C silicone lead wires

WIRING: Black 5 foot 18/2 zip cord from base of fixture (12v only) For 25 foot 16/2 fixture lead wire add -25F to catalog number. 120v Standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only) 12v only

MOUNTING: Back plate and hardware supplied

FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available

Brass - Unfinished brass. Optional finishes available

Stainless Steel - Brushed









SL-07-BRS

SL-07-SS

ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT		
SL-07-BLT	Cast Aluminum Surface Light	18w S8 #1141	1.0 lbs.		
SL-07-BRS	Cast Brass Surface Light	18w S8 #1141	1.0 lbs.		
SL-07-SS	316 Stainless Steel Surface Light	18w S8 #1141	1.0 lbs.		
SL-07-MR8-BLT	Cast Aluminum Surface Light	20w MR8 FL	1.0 lbs.		
SL-07-MR8-BRS	Cast Brass Surface Light	20w MR8 FL	1.0 lbs.		
SI_O7_MDQ_SS	316 Stainless Steel Surface Light	20w MP8 FI	1.0 lbs		

FOLLOWING -SP MODELS COME SUPPLIED WITH BLACK PVC TELESCOPIC POST FOR GROUND MOUNTING

SL-07-SP-BLT	Cast Aluminum Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-BRS	Cast Brass Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-SS	316 Stainless Surface Light, PVC Post	18w S8 #1141	1.0 lbs.
SL-07-SP-MR8-BLT	Cast Aluminum Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-BRS	Cast Brass Surface Light, PVC Post	20w MR8 FL	1.0 lbs.
SL-07-SP-MR8-SS	316 Steel Surface Light, PVC Post	20w MR8 FL	1.0 lbs.










LIGHT DISTRIBUTIONS AND PHOTON





METRICS					
Feet	3	6	9	12	
Meters	_ 1	2	3		Beam
20w MR8 23°FL	0.5 0.15 67.6 364	2.4 0.74 16.9 96	3.7 1/11 7.6 41	V	foot- candles

		LISTED
JOB INFORMATIO	N	
Туре:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		

		ronze exture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT -A	ATV -E	BRT	-CAM	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

SL-07 Cut Sheet 060314 **BRASS & COPPER ONLY**