

Catalog Number

Project

Type

Features & Specifications

Construction

Die cast zinc housing. Offered standard with either a die cast long shield or die cast flush shield.

Optical System

Clear, tempered glass lens. Designed specifically for bi-pin MR16 operation and can accommodate a variety of MR16 beam spreads.

Electrical System

MR16 ceramic bi-pin socket with heat shield. Fixture requires a low voltage transformer to supply power. Comes standard with 3' #18/2 wire lead and a low voltage connector.

Mounting

Fully adjustable die-cast threaded swivel arm. 1/2" threaded NPT. This fixture is suitable for use in an

UP LIGHT POSITION ONLY.

Finish

A Super Durable Polyester powder coat finish is electrostatically applied. Standard colors available: Black, Bronze, White, OD Green, US Green. Custom colors available upon request.

TLM16 SERIES Low Voltage MR16 Bullet up Light



Accessories

**B01
Tree
Base**



**B06
Brass
Tree
Base**



**B16-12
Palm Tree
Base with
12' Strap**



**SMSB
MMSB
LMSB
Mounting
Stakes**



**B10
1/2" Hub**



**TLSBBJ
B Brass
Junction
Box**



**TLL450B
TLL600B
Honeycomb
Louver**



Est Shipping Weight: 2 lbs

Ordering Nomenclature

Ex: (TLM16 Series Low Voltage MR16 Bullet, Long Shield, Black Finish = TLM16L-BK)

TLM16				
--------------	--	--	--	--

SERIES	SHIELD	FINISH	Accessories	Low Voltage Transformers
TLM16	L - Long Shield F - Flush Shield	BK - Black BZ - Bronze GRN - OD Green VRD - Verde WH - White SP - Special	B01 - Tree Base B06 - Brass Tree Base B16-12 - Palm Tree Base B10 - 1/2" Hub SMSB - Small Stake MMSB - Medium Stake LMSB - Large Stake TLSBBJB - Brass Junction Box TLL450B - Honeycomb Louver TLL600B - Honeycomb Louver	TLLET75-75W Transformer TLLET150 - 150W Transformer LV Transformer Enclosures LVSS300 - 300W Stainless Steel LVSS600 - 600W Stainless Steel LVSS900 - 900W Stainless Steel

Conforms to UL1838 Specifications

