HID-110-H-EX39-840-BYP-SB



Replace 250 - 400W HID lamps for shoebox area lights. Water/dust resistant. LED uses approximately 76% less energy than traditional HID lamps. Expandable flaps and rotatable base.

Color: White

Weight: 3.6 lbs

| Project: | Туре: |
|--------------|-------|
| Prepared By: | Date: |

Driver Info

Watts

110W Inpu

Color Temp 4000K (Cool

Lumens 13,800

Efficacy 125.5 LPW Color Accuracy 80 CRI

L70 Accuracy 50,000

LED Info

Input Voltage 100-277V Power Factor 0.9

Flicker <30% THDi <20%

R9

Technical Specifications

Listings

UL Listed:

Yes

UL Classified:

Yes FCC:

Yes

Rohs:

Yes

CEC Status:

Lawful for sale in California

DLC Qualified:

Yes

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: P0J6172M

Description

Lamp Type:

HID

Bulb Type:

Shoe Box

Base Type:

EX39, Mogul Base

Dimmable:

No

Construction

Operating Temperature:

-20 - 40°C

Bare Lamp Illuminated Length (inches):

7.17"

MOL (inches):

11.1"

MOD (inches):

4.92"

Minimum Compartment Size (inches):

Length: 11.02" Width: 11.02" Height: 9.84"

LED Characteristics

Lifespan:

50,000-hour LED lifespan based on IES LM-70

results

Optical

Beam Angle:

180°

Other

Warranty:

5-years

HID-110-H-EX39-840-BYP-SB

Technical Specifications (continued)

Other

Accessories:

Surge protector available. Click here for surge protector accessory. Sold separately.

Shipping Information

11 1/8" 282mm

Case Qty:

Dimensions

Case Dimensions:

17.52 x 13.27 x 13.58

Pallet Quantity of Pieces:

Pallet Dimensions:

28.5 x 37.01 x 45.47

Features

HID REPLACEMENT - Replacement for conventional HID lamps BALLAST BYPASS - Internal driver eliminates the need for external driver or ballast

COMPACT DESIGN - Allows the lamp to fit in most fixtures

EXPANDABLE FLAPS - Provides the light where you need it

HEAT DISSIPATION - Thermal technology extends lifespan

WATER & DUST RESISTANT - Ideal for outdoor fixtures

ENCLOSED FIXTURE RATED - May be used in enclosed and open

ENERGY SAVINGS - Uses 76% less energy than traditional lamps SURGE PROTECTION - Includes 4kV surge protection

MERCURY FREE - Environmentally friendly vs fluorescent

technologies 350° ROTATABLE BASE - Direct light where needed

Ordering Matrix

| Family | Lamp Power | Orientation | Base Type | CRI | Color Temp | Installation Type | Lamp Type |
|--------|---------------------------------------|-----------------------|--------------------|------------|---|-------------------|--------------|
| HID | 110 | Н | EX39 | 8 | 40 | BYP | SB |
| | 80 = 320W 110 = 400W | H = Horizontal | EX39 = EX39 | 8 = 80 CRI | 30 = 3000K 40 = 4000K 50 = 5000K | BYP = Bypass | SB = Shoebox |

HID-110-H-EX39-850-BYP-SB



Replace 250 - 400W HID lamps for shoebox area lights. Water/dust resistant. LED uses approximately 76% less energy than traditional HID lamps. Expandable flaps and rotatable base.

Color: White

Weight: 3.6 lbs

| Project: | Туре: |
|--------------|-------|
| Prepared By: | Date: |

 Driver Info
 LED Info

 Watts
 110W
 Input Voltage 100-277V

 Color Temp
 5000K (Daylight)
 Power Factor 0.9

 Lumens
 13,800
 Flicker
 <30%</td>

 Efficacy
 125.5 LPW
 THDi
 <20%</td>

Color Accuracy 80 CRI

L70 Accuracy 50,000

Technical Specifications

Listings

UL Listed:

Yes

UL Classified:

Yes FCC:

Yes

Rohs:

Yes

CEC Status:

Lawful for sale in California

DLC Qualified:

Yes

DLC Listed:

This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. DLC Product Code: POTO54B5

Description

Lamp Type:

HID

Bulb Type:

Shoe Box

Base Type:

EX39, Mogul Base

Dimmable:

No

Construction

Operating Temperature:

-20 - 40°C

Bare Lamp Illuminated Length (inches):

7.17"

MOL (inches):

11.1"

MOD (inches):

4.92"

Minimum Compartment Size (inches):

Length: 11.02" Width: 11.02" Height: 9.84"

LED Characteristics

Lifespan:

50,000-hour LED lifespan based on IES LM-70

results
Optical

Beam Angle:

180°

Other

Warranty:

5-years

HID-110-H-EX39-850-BYP-SB

Technical Specifications (continued)

Other

Accessories:

Surge protector available. Click <u>here for surge</u> protector accessory. Sold separately.

Shipping Information

Case Qty:

6

Case Dimensions:

17.52 x 13.27 x 13.58

Pallet Quantity of Pieces:

72

Pallet Dimensions:

28.5 x 37.01 x 45.47

Features

HID REPLACEMENT - Replacement for conventional HID lamps
BALLAST BYPASS - Internal driver eliminates the need for external driver or ballast

 $\label{lem:compact_def} \mbox{COMPACT DESIGN - Allows the lamp to fit in most fixtures}$

EXPANDABLE FLAPS - Provides the light where you need it

HEAT DISSIPATION - Thermal technology extends lifespan

WATER & DUST RESISTANT - Ideal for outdoor fixtures

ENCLOSED FIXTURE RATED - May be used in enclosed and open fixtures

ENERGY SAVINGS - Uses 76% less energy than traditional lamps

SURGE PROTECTION - Includes 4kV surge protection

MERCURY FREE - Environmentally friendly vs fluorescent technologies

350° ROTATABLE BASE - Direct light where needed

7 3/16' 182mm 9° 229mm 229mm 11.1/8' 282mm 282mm

| Orderin | ng Matrix | | | | | | |
|---------|---------------------------------------|-----------------------|--------------------|------------|---|-------------------|--------------|
| Family | Lamp Power | Orientation | Base Type | CRI | Color Temp | Installation Type | Lamp Type |
| HID | 110 | Н | EX39 | 8 | 50 | BYP | SB |
| | 80 = 320W 110 = 400W | H = Horizontal | EX39 = EX39 | 8 = 80 CRI | 30 = 3000K 40 = 4000K 50 = 5000K | BYP = Bypass | SB = Shoebox |