

LED THE SPOT SL-18
SURFACE STEP LIGHTS





SURFACE STEP LIGHTS

SL-18 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Cast aluminum or cast brass one piece construction, (no back plate)

LENS: None

LAMP SUPPLIED: 18w S8 #1141; 1200 hours average rating (25w max.)

LAMP OPTIONS: We recommend 3w 50,000 hours average rating OMNI-3 LED (-LED3) or OMNI-3 Super Saver (-LED3SS) 10,000 hours average rating 20w Xenon (-X) or 20w Halogen (-H))) 120v: 15w T7 or 25w T8

SOCKET: Single contact bayonet, brass nickel plated lamp socket screw shell (Ba15s); double contact bayonet base (Ba15d) for 120v, both with 200°C silicone lead wires

WIRING: Black 5 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

120v Standard wiring

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only) 12v only

MOUNTING: None required


FINISH: Aluminum - Black texture polyester powder coat. Optional finishes available
Brass - Unfinished brass. Optional finishes available




SL-18-BRS

ORDERING INFORMATION


CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-18-BLT	Cast Aluminum Surface Light	18w S8 #1141	1.0 lbs.
SL-18-BRS	Cast Brass Surface Light	18w S8 #1141	2.0 lbs.



LIGHT DISTRIBUTIONS AND PHOTOMETRICS



SL-18 Half Spread Photometrics



SL-18 Half Spread Photometrics



Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT