

Catalog Number	
Project	Type

FEATURES & SPECIFICATIONS

CONSTRUCTION — Made with a die cast aluminum housing with stainless steel fasteners. Designed to efficiently operate PAR30 lamps. A high temperature drain plug is provided for uplight applications. A sturdy knuckle mount with locknut is provided for a secure installation. ETL listed for wet locations.

FINISH — A Super Durable Polyester powder coat finish is electrostatically applied in our state of the art paint facility. Standard colors available: Black, Bronze, OD Green, White. Custom colors available upon request.

OPTICAL SYSTEM — Beam spreads vary based on the light source and lamp shape chosen. Standard shields include an up shield with a convex clear tempered glass lens and an open down shield. Various additional shield and lens assemblies are available for custom applications. A shield should be ordered to complete the assembly and ordered separately.

ELECTRICAL SYSTEM — LED PAR lamp models available for line voltage operation. Recommended to use minimum one surge protection device per circuit. Each fixture comes with a medium base porcelain 4KV rated socket positioned for PAR30 use.

MOUNTING — Comes standard with a 1/2" threaded knuckle mount, fully adjustable swivel arm, and locking teeth. The fixture can be mounted using a Techlight mounting accessory. See page 2.

R3AG SERIES

Medium R30 Aluminum Bullet for LED PAR30



ORDERING INFORMATION

Choose the bold face options for the appropriate luminaire configuration for your application and enter on the line above each fixture attribute. Accessories may be factory installed, depending on the particular accessory chosen, but still be ordered as a separate line item.

EXAMPLE:

R3AG ODG

R3AG	
SERIES	FINISH
	BZ = Bronze BK = Black GR = US Green WH = White ODG = Olive Drab Green SP² = Special

SHIELDS (Order as separate line items, specify shield finish as suffix)

S3DN	Down shield
S4UP	Up shield with convex lens and molded silicone gasket
S5	Down Statue/Spot/Tube
S5UP	Up Statue/Spot/Tube with convex lens and molded silicone gasket
S6DN	Down shield with ring
S32DN	Down Shield With Lens
S48DN	Down shield with blue lens and molded silicone gasket
S49UP	Up shield with blue lens
S4-CA	Die cast aluminum up shield with convex lens and molded silicone gasket
S5-P¹	Premium tube lens

Specify shield finish as suffix from options in the ordering chart to the left.
Example: S3DN ODG

ACCESSORIES (Order as separate line items)

BASE

B01GL	Tree Base With Ground Lug
B02	1/2" Conduit Base
B03	3-Hole Round Cover
B06	Brass Tree Base
B10	1/2" Hub With Ground
B16-12	Palm Tree Base With 12' Strap
LMSB	20" X 2.5" Mounting Stake (Brass)
S81	Honeycomb Louver
TLSBBJB	Brass Junction Box
TLHB800RCH	Digital Timer
PSJ163	16 Gauge 3 Strand Lead Wire (Color Coded) Per Linear Foot

LAMPS (Order as separate line items)

LUVPAR3012WXXK^{3,4}	LED 12W PAR30
ALUMAPAR3012WxxK^{3,5}	LED 12W PAR30


NOTES

- 1 = Premium shields are designed to allow debris to wash free in an uplight position.
- 2 = Custom RAL color matching is available. Contact your sales representative for additional info.
- 3 = Recommend minimum one surge protection device for each circuit. See [FSPENCA27TV Series](#) specification sheet for details.
- 4 = XX could be 40 = 4000K or GR = Green Lens. See [LUV Series](#) specification sheet for details.
- 5 = XX could be 30 = 3000K, 65 = 6500K or MVS = Moonlight. See [ALUMA-LUX](#) Series specification sheet for details.

R3AG Medium R30 Aluminum Bullet


AVAILABLE FIXTURE DIMENSIONS

Dimensions shown are for fixture bodies only. Mounting options must be ordered separately.



ADDITIONAL ACCESSORIES

S81
Honeycomb Louver



TLHB800RCH
Digital Timer



PSJ163
16 Gauge 3 Strand Lead Wire



MOUNTING ACCESSORIES

B01GL
Tree Base with Ground Lug



B02
1/2" Conduit Base



B03
4" Round 3 Hole Cover



TLSBBJB
Brass Junction Box



B16-12
Palm Tree Base with 12' Strap



B06
Brass Tree Base



B10
1/2" Hub with Ground



SMSB, MMSB, LMSB
12" x 1" Mounting Stake (Brass)
18" x 1" Mounting Stake (Brass)
20" x 2.5" Mounting Stake (Brass)



← Natural Brass Cap

← Black SCH 40 PVC Pipe


SURGE PROTECTION DEVICE

FSPENCA277V⁴ - 10kA surge protector device (**102549**) with aluminum enclosure


102549 - 10kA Surge Protective Device

- 90-305 Vac Working Input Voltage
- 15 kA Maximum, 10 kA Nominal (15 strikes) Surge Current Rating Using Industry Standard 8/20us Wave
- UL1449 Type 4, EN 61643-11 - Surge Protective Devices T2 & T3
- IEEE C62.41.2 Location Category C High
- High Temperature, 85C Maximum Ambient
- Flameproof Plastic Enclosure
- IP66
- Compatible with Inventronics LED Drivers
- "Series" Wiring Configuration

102549 DIMENSIONS



102549 WIRING DIAGRAM (IN SERIES)



WARNING: Maintenance performed including the replacement of LED bricks while power is still supplied to the luminaire may result in system failures and will void the warranty.



TECHLIGHT
INNOVATION IN ILLUMINATION

2009 McKenzie Drive Suite 110 | Carrollton, TX 75006 | PH: 800.225.0727 www.techlight.com











All dimensions and specifications are subject to change without notice.

REV: 20260224-10

R3AG Medium R30 Aluminum Bullet

SHIELDS

Specify shield finish as suffix from options in the ordering chart on page 1.
Example: S3DN ODG

UP SHIELDS	DOWN SHIELDS	TUBES
S4UP = Up shield with convex lens and molded silicone gasket  3.84" R2.21"	S3DN = Down shield  2.00" 0.5" 9.00" R2.23"	S5 = Down Statue/Spot/Tube  5.00" R2.21"
S5UP = Up Statue/Spot/Tube with convex lens and molded silicone gasket  5.00" R2.21"	S6DN = Down shield with ring  2.25" 0.19" 8.00" R2.21"	S5-P = Premium tube lens  5.00" R2.21"
S49UP = Up shield with blue lens  2.17" 3.34" R2.21"	S32DN = Down Shield With Lens  2.25" 0.19" 8.83" R2.21"	
S4-CA = Die cast aluminum up shield with convex lens and molded silicone gasket  3.75" 1.051" R2.27"	S48DN = Down shield with blue lens and molded silicone gasket  2.25" 8.83" R2.21"	

WARNING: Maintenance performed including the replacement of LED bricks while power is still supplied to the luminaire may result in system failures and will void the warranty.



TECHLIGHT
 INNOVATION IN ILLUMINATION

2009 McKenzie Drive Suite 110 | Carrollton, TX 75006 | PH: 800.225.0727 www.techlight.com

All dimensions and specifications are subject to change without notice.

REV: 20260224-10