

CIRCULAR PAVER LIGHTS SL-37-P-MR16 SERIES



TYPE

SPECIFICATIONS

CONSTRUCTION: Machined brass cylinder with threaded cap

LENS: High impact clear tempered step glass O-RING: High temperature red silicone

LAMP SUPPLIED: 40,000 hour 3w ARROW Super Saver MR16 LED (-LED3) LAMP OPTIONS: We recommend 40,000 hour 5w (-LED5) or 7w (-LED7) ARROW

Super Saver MR16 LED

SOCKET: High temperature ceramic bi-pin with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable

(12/2, 10/2 or 8/2 only)

FINISH: Unfinished brass. Optional finishes available

VEHICULAR PRESSURE RATING: 8800 lbs









ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
SL-37-P-MR16-LED3-BRS	Circular Brass Paver Light	3w MR16 LED 36° FL	2.0 lbs.



SL-37-P-MR16





		Intertek
JOB INFORMATION		
Туре:	Date:	
Job Name:		
Cat. No.:		
Lamp(s):		
Specifier:		
Contractor:		
Notes:		
FOCUS INDUSTRIES INC. 25301 COMMERCENTRE DRIVE LAKE FOREST, CA 92630		sindustries.com sindustries.com (949) 830-3390

Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder		lcid lust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-САМ	-WTX	-НТХ	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAI	R/CAR	-BAV/CAV	-BAT
								_							

SL37PIVR16Cu6heet 120718 BRASS & COPPER ONLY