

DIRECTIONAL LIGHTS

DL-50-PAR30 Series



TYPE

SPECIFICATIONS

CONSTRUCTION:

ALUMINUM: Aluminum bullet; matching cast aluminum adjustable swivel with 240° rotation

BRASS: Brass bullet; matching cast brass adjustable swivel with 240° rotation

LENS: High impact clear tempered convex glass

O-RING: High temperature red silicone

LAMP SUPPLIED: None (75w max); Use only outdoor rated PAR30 lamps

We recommend 12w PAR30 Super Saver LED, 40,000 hours. 1080 lumens

SOCKET: High temperature ceramic medium base with 250° C silicone lead wires

WIRING: Standard 120 volt Black, White and Ground 9" lead wires

MOUNTING: None supplied. We recommend FA-26 mounting pedestal

FINISH: Aluminum - Black texture polyester powder coat, optional finishes available


Brass - Unfinished, optional finishes available

GO GREEN



ORDERING INFORMATION

CATALOG NO.	DESCRIPTION	LAMP	SHIP WEIGHT
DL-50-PAR30NL-BLT	Aluminum PAR30 Bullet	None	3.0 lbs.
DL-50-PAR30NL-BRS	Brass PAR30 Bullet	None	5.0 lbs.



DL-50-PAR30

IP65

CE

ETL LISTED US

BEAM/GLARE CONTROL ACCESSORIES

FA-08-06	Round 1/4" Hex Cell Louver
FA-10-30-BLUE	Blue Tempered Glass Lens
FA-10-30-GREEN	Green Tempered Glass Lens
FA-98-50	Linear Spread Tempered Glass Lens
FA-104-50	Wide Spread Tempered Glass Lens Softener



Black Texture (Standard)	Antique Verde	Bronze Texture	Camel	White Texture	Hunter Texture	Rust	Weathered Iron	Weathered Brown	Stucco	Rubbed Verde	Chrome Powder	Acid Rust	Acid Verde	Black Acid Treatment
-BLT	-ATV	-BRT	-CAM	-WTX	-HTX	-RST	-WIR	-WBR	-STU	-RBV	-CPR	-BAR/CAR	-BAV/CAV	-BAT

DIRECTIONAL LIGHTS

DL-50-LEDM17

TYPE

MOUNTING ACCESSORIES

