



DL-13 SERIES SPECIFICATIONS:

CONSTRUCTION: Cast aluminum or cast brass Bullet; matching cast aluminum or brass adjustable swivel

LENS: High impact clear tempered convex glass

LED SUPPLIED: 4w 50,000 hrs ARROW LED

LED OPTIONS: 6w 50,000 hrs ARROW LED or 4w ARROW Saver LED 40,000 hours average rating

LEGACY LAMP OPTIONS: 20w MR16 ULTRA 10,000 hours average rating;

20w MR16 TITAN 18,000 hours average rating

SOCKET: High temperature ceramic bi-pin GU5.3 with 250°C silicone lead wires

WIRING: Black 3 foot 18/2 zip cord from base of fixture (12v only)

For 25 foot 16/2 fixture lead wire add -25F to catalog number.

CONNECTION: FA-05 Quick Connector (not supplied) from fixture to main cable (12/2, 10/2 or 8/2 only)


MOUNTING: FA-03 black 9" ABS stake threaded 1/2" NPS

FINISH: Aluminum-Black texture polyester powder coat. Optional finishes available
Brass-Unfinished brass. Optional finishes available

| Catalog Number | Description |
|----------------|--------------------|
| DL-13-LEDBLT | 2.6" Bullet (MR16) |
| DL-13-LEDBRS | 2.6" Bullet (MR16) |

RECOMMENDED ENHANCEMENTS FOR DL-13 SERIES:

- FA-08-21 Round 1/8" Hex Cell Louver
- FA-11-AMBER Amber Tempered Glass Lens
- FA-11-BLUE Blue Tempered Glass Lens
- FA-11-GREEN Green Tempered Glass Lens
- FA-11-RED Red Tempered Glass Lens
- FA-98 Linear Spread Tempered Glass Lens
- FA-104 Wide Spread Tempered Glass Lens Softener



DL-13-LEDBLT
4w ARROW MR16 LED
Cast Aluminum

