

Supplied w/ (1) LP930 End Cap.



"Application: Extruded aluminum track with 20-Amp rated flat, solid copper conductors. Provides for mounting and power to adjustbale track heads. Light fixtures can be positioned without any needs for tools. Compatible with most H-type track lighting heads.

Electrical: Single circuit: 2400 watts.

Saftey Labels: Dry Location Only.

Length: Available in 12' Channel, 2' Channel, 4' Channel, 6' Channel and 8' Channel***.

Finish: Available in White***, Bright White, Black and Natural Metal**.

Label: UL Listed, cETL Listed



COMPATIBILITY

COMI ATIDILITI		
\$	7775 4119	(B)
<u>LP943</u>	<u>LP989</u>	<u>LP931</u>
L-CONNECTOR	CONDUIT CONTINUATION KIT	LIVE END W/ CANOPY
	(RO)	Ø
<u>LP917</u>	<u>LP983</u>	<u>LP930</u>
SLOPE CEILING TRACK Adapter	T-BAR CLIP	END CAP
€ 2	2. 425 (*
LP949	<u>LP950</u>	<u>LP957</u>
MINI CONNECTOR	CORD & PLUG Connector	PENDANT ADAPTER
		#5
<u>LP946</u>	<u>LP980</u>	<u>LPO</u>
X-CONNECTOR	CONDUIT CONNECTOR	PENDANT ASSEMBLY KIT
	e.	ł
LTD50	<u>LP902</u>	<u>LP9</u>
17W/25W COB ECOTRACK LED	FLEXIBLE CONNECTOR	LINE VOLTAGE Extension Wand

Please see website for more compatible items.

FEATURE:





LP	LENGTH		FINISH	
LP	02	:2' Channel	W	:White**
	04	:4' Channel	W-2	:Bright White
	06	:6' Channel***	В	:Black
	80	:8' Channel***	N	:Natural Metal*
	12	·12 Channel**	*	

ID#: 700



ORDERING EXAMPLE: LP06B

^{*} Natural Finish Not available for 12' Section
** White Finish Not available for 8' Section, Only Bright White, Black and Natural
***SPECIAL HANDLING FEE FOR SHIPMENTS 6 PIECES OR LESS