



SPECIFICATION SHEET

120 VAC Multi-Tap



FEATURES

- 10 YEAR FREE REPLACEMENT WARRANTY
- FULLY DIMMABLE WITH LOW-VOLTAGE MAGNETIC DIMMER
- 1/8" STEEL, POWDER COATED NEMA 3R CASE
- STANDARD WITH MANDATORY SECONDARY PROTECTION
- PRIMARY LINE CORD AVAILABLE. CONSULT FACTORY
- 12—15VAC MULTI-TAP SECONDARY
- MEETS OR EXCEEDS ALL UL, CUL, ANSI/UL, CSA REQUIREMENTS

REQUIREMENTS



- ETL/cETL LISTED. FCC, RoHS
- MANDATORY SECONDARY PROTECTION AS STATED IN THE NATIONAL ELECTRIC CODE ARTICLE 411 (1993, 1996, 1999, 2002, 2005, AND 2008)
- MAY BE USED WITH INDIVIDUAL "LISTED" COMPONENTS TO MEET SYSTEM REQUIREMENTS AS LONG AS ALL PARTS ARE LISTED TO SAME ANSI/UL STANDARD

PART NUMBER	1023-12-MT	1101-12-MT	1102-12-MT
PRIMARY VOLTAGE	120VAC	120VAC	120VAC
OUTPUT VOLTAGE	12 - 15VAC / 12.5A	12 - 15VAC / 25A	12 - 15VAC / 50A
FREQUENCY	60Hz	60Hz	60Hz
WATTAGE	100/150 Watts	300 Watts	600 Watts (2x300)
DIMENSIONS	9.65" x 4.35" x 3.86"	9.65" x 4.35" x 3.86"	11" x 4.05" x 2.2"
WEIGHT	12 LBS	15 LBS	21 LBS

WWW.SEBCOINDUSTRIES.COM

TEXAS OFFICE (817) 464-0145